
Directions for Downloading the Full Report



To download the full report, visit

https://kdotapp.ksdot.org/kdotlib/kdotlib2.aspx

1. Enter KS-17-03

2. Click the Search button to the right of the search box.

- 3. You may have to scroll to find the specific report.
- 4. To download the report, click on the title of the report to open the PDF file and save it to your hard drive.

Displaying results 1 - 2 of 2						
Document Title	Reference Name(s)	1 Date	Filesize	Reference Number	Comments	Request Copy
Guardrail and Bridge Rail Recommendations for Very Low Volume Local Roads in Kansas: Addendum to Include Bridges Up to 100 Feet Long and Traffic Volume Up to 100 Vehicles Per Day Final Report	Bureau of Local Projects & Bureau of Research & KDOT & Ronald Seitz & Tod Salfrank	7/1/2017	4mb	KS-17-03	Full report available electronically only.	<u>Request Copy</u>
Guardrail and Bridge Rail Recommendations for Very Low Volume Local Roads in Kansas. Addendum to Include Bridges Up to 100 Feet Long and Traffic Volume Up to 100 Vehicles Per Day Summary Report	Bureau of Local Projects & Bureau of Research & KDOT & Ronald Seitz & Tod Salfrank	7/1/2017	574.7kb	KS-17-03	Full summary report available electronically only.	<u>Request Copy</u>
		1				

If you have any questions, please email KDOT#Research.Library@ks.gov


Report No. KS-17-03 = FINAL REPORT = July 2017

Guardrail and Bridge Rail Recommendations for Very Low-Volume Local Roads in Kansas: Addendum to Include Bridges Up to 100 Feet Long and Traffic Volume Up to 100 Vehicles Per Day

Ronald J. Seitz, P.E. Division of Engineering & Design

Tod Salfrank Bureau of Local Projects

Kansas Department of Transportation





1	Report No. KS-17-03	2 Government Accession No.	3	Recipient Catalog No.		
4	KS-17-05 Title and Subtitle Guardrail and Bridge Rail Recommendations for Very Low-Volume Local Roads			Report Date July 2017		
	in Kansas: Addendum to Include Bridges Up to 100 Feet Long and Traffic Volume Up to 100 Vehicles Per Day			Performing Organization Code		
7	Author(s) Ronald J. Seitz, P.E., Tod Salfrank		7	Performing Organization Report No.		
9	Performing Organization Name and Address Kansas Department of Transportation			Work Unit No. (TRAIS)		
	Bureau of Local Projects 700 SW Harrison Street 3rd Floor Wes Topeka, Kansas 66603-3745	t	11	Contract or Grant No.		
12			13	Type of Report and Period Covered Final Report		
	Topeka, Kansas 66611-1195		14	Sponsoring Agency Code		

15 Supplementary Notes

For more information write to address in block 9.

This report is an addendum to a previous report, KS-14-16, available at <u>http://kdotapp.ksdot.org/kdotlib/kdotlib2.aspx</u> or by contacting <u>KDOT#Research.Library@ks.gov</u>.

In 2014, the Kansas Department of Transportation undertook a study, entitled "Guardrail and Bridge Rail Recommendations for Very Low-Volume Local Roads in Kansas" (Report No. KS-14-16, Seitz & Salfrank, 2014), to establish practical risk-based guidelines and policies for bridge rails and guardrails on low-volume local roads in the state.

The purpose of the effort outlined in this report is to expand on the work performed in the 2014 study and to supplement the recommendations to include bridges up to 100 feet in length and roads with ADT up to 100 vehicles per day. The primary tasks to be completed will include:

- Analysis of bridge rail/guardrail crashes on bridges with length between 50 feet and 100 feet and located on a local road with ADT between 50 and 100 vehicles per day.
- Benefit-cost analyses based on these parameters and typical location features.

Based on the results of this study, it is recommended that the recommendations of Report No. KS-14-16 be expanded to include bridge rails installed on new or rehabilitated bridges up to 100 feet long with traffic volume up to 100 vpd.

17 Key Words Low Volume Roads, Rural, Guardrail, Bridge Rail, Local Government		18	Distribution Statement No restrictions. This document is available to the public through the National Technical Information Service www.ntis.gov.				
19 Security Classification (of this report) Unclassified	20 Security Classification (of this page) Unclassified	21	No. of pages 158	22 Price			

Form DOT F 1700.7 (8-72)

This page intentionally left blank.

Guardrail and Bridge Rail Recommendations for Very Low-Volume Local Roads in Kansas: Addendum to Include Bridges Up to 100 Feet Long and Traffic Volume Up to 100 Vehicles Per Day

Final Report

Prepared by

Ronald J. Seitz, P.E. Director, Division of Engineering & Design

Tod Salfrank Assistant Chief, Bureau of Local Projects

Kansas Department of Transportation

A Report on Research Sponsored by

THE KANSAS DEPARTMENT OF TRANSPORTATION TOPEKA, KANSAS

July 2017

© Copyright 2017, Kansas Department of Transportation

NOTICE

The authors and the state of Kansas do not endorse products or manufacturers. Trade and manufacturers names appear herein solely because they are considered essential to the object of this report.

This information is available in alternative accessible formats. To obtain an alternative format, contact the Office of Public Affairs, Kansas Department of Transportation, 700 SW Harrison, 2nd Floor – West Wing, Topeka, Kansas 66603-3745 or phone (785) 296-3585 (Voice) (TDD).

DISCLAIMER

The contents of this report reflect the views of the authors who are responsible for the facts and accuracy of the data presented herein. The contents do not necessarily reflect the views or the policies of the state of Kansas. This report does not constitute a standard, specification or regulation.

Abstract

In 2014, the Kansas Department of Transportation undertook a study, entitled "Guardrail and Bridge Rail Recommendations for Very Low-Volume Local Roads in Kansas" (Report No. KS-14-16, Seitz & Salfrank, 2014), to establish practical risk-based guidelines and policies for bridge rails and guardrails on low-volume local roads in the state.

The purpose of the effort outlined in this report is to expand on the work performed in the 2014 study and to supplement the recommendations to include bridges up to 100 feet in length and roads with ADT up to 100 vehicles per day. The primary tasks to be completed will include:

- Analysis of bridge rail/guardrail crashes on bridges with length between 50 feet and 100 feet and located on a local road with ADT between 50 and 100 vehicles per day.
- Benefit-cost analyses based on these parameters and typical location features.

Based on the results of this study, it is recommended that the recommendations of Report No. KS-14-16 be expanded to include bridge rails installed on new or rehabilitated bridges up to 100 feet long with traffic volume up to 100 vpd.

Table of Contents

Abstract
Table of Contents
List of Tables
Introduction1
Kansas Bridge Crash Data Collection and Review
Benefit Cost Analyses
Conclusions
Recommendations
References
Bibliography
Appendix A: Fatal Crashes
Appendix B: Serious Injury Crashes
Appendix C: Non-Fatal or Serious Injury Crashes 19
Appendix D: Crash Reports, Fatal Crashes at Short Bridges on Low-Volume Local Roads 53
Appendix E: Crash Reports, Serious Injury Crashes at Short Bridges on Low-Volume
Local Roads
Appendix G: Benefit/Cost Analyses Using RSAP Version 2.03
Appendix H: Benefit/Cost Analyses Using RSAP Version 3.01 105

Note: Appendix F contains no additional information to the original study

List of Tables

Table 1: Summary of Crash Review 2008–2014, Low-Volume Road Bridge Crashes	3
Table 2: Traffic Volume and Bridge Length by Category	4
Table 3: Annual Probability of Reported Crash	5
Table 4: Annual Probability of Fatal or Serious Injury Crash	5
Table 5: RSAP 2.0.3 B/C Results for 20-Foot-Long Bridge	7
Table 6. RSAP 2.0.3 B/C Results for a 50-Foot-Long Bridge	7
Table 7. RSAP 2.0.3 B/C Results for a 100-Foot-Long Bridge	7
Table 8: RSAP 3.0.1 B/C Results for a 20-Foot-Long Bridge	8
Table 9: RSAP 3.0.1 B/C Results for a 50-Foot-Long Bridge	8
Table 10: RSAP 3.0.1 B/C Results for a 100-Foot-Long Bridge	8